

## Pennzoil® High Mileage Vehicle™ Motor Oil 20W-50

### Product Description

Pennzoil® High Mileage Vehicle™ Motor Oil is formulated to meet the needs of high mileage vehicles. Vehicles that have accumulated over 75,000 miles sometimes see an increase in oil consumption or increase in leaks.

Pennzoil® High Mileage Vehicle™ Motor Oil is a low-volatility oil that helps decrease oil consumption.

Pennzoil® High Mileage Vehicle™ Motor Oil is blended to the higher end of the viscosity range, and incorporates a special seal-conditioning agent that helps reduce leaks.

### Application

Pennzoil® High Mileage Vehicle™ Motor Oil is recommended for all gasoline engines used in passenger cars and light trucks. Pennzoil® High Mileage Vehicle™ Motor Oil exceeds the current API Service SM and may be used in old or new vehicles.

### Benefits

- Helps reduce oil consumption
- Special seal-conditioning additive helps reduce leaks
- Low volatility
- Helps improve engine performance
- Exceeds API Service SM, SL, SJ

### Typical Physical and Chemical Properties

#### Pennzoil® High Mileage Vehicle™ Motor Oil

Test	Method	Typical Results
Viscosity Grade		20W-50
API Service		SM
Gravity, °API	ASTM D-287	29.3
Specific Gravity @ 60°F(15.6°C)	ASTM D-287	0.89
@ 40°C, cSt	ASTM D-445	190.6
@ 100°C, cSt	ASTM D-445	21.0
Viscosity Index	ASTM D-2270	130
Flash Point, °C(°F)	ASTM D-93	196
Pour Point, °C(°F)	ASTM D-97	-21
CCS Viscosity, cP (°C)	ASTM D-5293	7,040(-15)
MRV Viscosity, cP (°C)	ASTM D-4684	21,300(-20)
HT/HS Viscosity, cP	ASTM D-4683	5.3
Noack Volatility, %	ASTM D-5800	5.0

These characteristics are typical of current production.

Whilst future production will conform to Pennzoil's specification, minor variations in these characteristics may occur.



Not just oil, Pennzoil.™